



High-Performance Oil for Limited Slip Gear Oil

SAE 80W-90 API GL-5



* DESCRIPTION

These are multi-purpose, premium-grade gear lubricants formulated from high-viscosity index paraffinic base oils and enhanced with a unique extreme-pressure additive that prevents wear. They also contain inhibitors for oxidation, corrosion and foaming.

These lubricants are ideal for most types of automotive and industrial bearings and gears, particularly those operating under severe temperature and load conditions. They are fully suitable for limited-slip differential applications.

They provide outstanding wear protection, even in the presence of small amounts of water and are recommended for use in truck transmissions and axles.

* BENEFITS / PROPERTIES

- Reduced wear.
- Slow and high operating temperatures.
- Seal compatibility.
- One product for both axles and transmissions.

* APPLICATIONS


Meets the performance requirements of **MIL-L-2105E**, **MACK GO-G** and **GO-H**, and the **GL-5** service classification.

TYPICAL CHARACTERISTICS

Super DRIVE® 80W-90 API GL-5

Appearance	-----	Bright & Clear
Specific Gravity @ 20/4 °C	ASTM D 1298	0.87
Kinematic viscosity cSt @ 40 °C cSt @ 100 °C	ASTM D 445	143 14.3
Flash Point, °C	ASTM D 92	210
Viscosity Index	ASTM D 2270	95
Pour Point	ASTM D 97	-25
Water Content, ppm	ASTM D 95	<100 ppm

AVAILABLE IN:



**5 gal. Pail (19 L)*



**55 gal drum (208 L)*



**264 gal. IBC (1,000 L)*

