



Continuously Variable Transmission Fluid

CVT



* DESCRIPTION

Super DRIVE® CVT is a fully synthetic fluid for continuously variable transmissions. **Super DRIVE® CVT** delivers equal or superior performance compared to most CVT fluids distributed by various OEMs (Original Equipment Manufacturers). It offers high anti-vibration performance for smoother and quieter gear shifts, while providing exceptional protection against oxidation and wear in most CVT brands. It meets and exceeds the JASO M349 LVFA durability standard at 80°C.

* BENEFITS / PROPERTIES

- Compatible with most vehicles, optimizing performance and passing BOSCH BELT BOX tests.
- Superior and extended anti-vibration and friction protection, ensuring unmatched driving comfort.
- Contains extreme pressure and anti-wear additives for optimal transmission protection.
- Excellent oxidation stability, extending lubricant life and service intervals.
- Outstanding compatibility with most seal types, helping prevent leaks.

* APPLICATIONS

Super DRIVE® CVT is formulated with a specialized additive package and backed by Belherr Engineering expertise to produce a continuously variable transmission fluid that meets the most demanding requirements of a wide range of vehicles equipped with push belts and CVT systems.

TYPICAL CHARACTERISTICS

Super DRIVE® CVT		
Color	VISUAL	Amber
Specific Gravity @ 25 °C	ASTM D 1298	0.854
Kinematic Viscosity cSt @ 40 °C cSt @ 100 °C	ASTM D 445	37.0 7.3
Viscosity Index	ASTM D 2270	167
Flash Point, °C	ASTM D 92	> 230
Pour Point, °C	ASTM D 97	- 49

AVAILABLE IN:



**US Quart: 0.946 L*




**5 gal. Pail (19 L)*



**US Gal 3.785 L*



**55 gal. Drum (208 L)*



**5.0 Lt container*



**264 gal. IBC (1000 L)*

