



Full synthetic drivetrain lubricant

SYN SAE 75W-90 API GL-5



BELHER®

*** DESCRIPTION**

Super Drive® SYN SAE 75W-90 API GL-5 is a fully synthetic oil for mechanical transmissions. It is designed for use in gear systems requiring lubricants with outstanding load-carrying capacity. Its synthetic formulation helps extend maintenance service intervals.

*** BENEFITS / PROPERTIES**

- **Super Drive® SYN SAE 75W-90 API GL-5** contributes to cost savings by reducing the frequency of oil changes thanks to its durability.
- Compatible with conventional seals and gaskets.
- Reduced bearing and gear wear compared to mineral oils.
- Significantly lowers the risk of fire and explosion compared to mineral oils.
- Superior low-temperature fluidity compared to mineral oils.
- Meets or exceeds the following specifications: SAE J2360, Mack GO-J Plus, FLENDER T 7302, ZF TE-ML (05A, 12L, 12N, 16F, 17B, 19C, 21A), API GL-5, MT-1, ISUZU (axles, large manual transmissions, LCV front axle).

*** APPLICATIONS**


Super Drive® SYN SAE 75W-90 API GL-5 is recommended for manual transmissions, final drives, and heavy-duty axles requiring API GL-5 and MT-1 performance. It is also suitable for helical and hypoid gears operating under severe conditions with high/low speeds and shock loads, as well as winch reduction gears.

TYPICAL CHARACTERISTICS

Super DRIVE® SAE 75W-90 API GL-5

Specific Gravity, 20/4 °C	ASTM D 1298	0.8560
Kinematic Viscosity cSt @ 40 °C cSt @ 100 °C	ASTM 445	115 17.3
Pour Point, °C	ASTM D 97	-42
Flash Point, °C	ASTM D 92	230
Copper strip corrosion 24h @ 100 °C	ASTM D 130	1A
ASTM Color	ASTM D 1500	2
Viscosity Index	ASTM D 2270	165

AVAILABLE IN:



***5 gal. Pail (19 L)**



***55 gal. Drum (208 L)**



***264 gal. IBC (1000 L)**

