

* DESCRIPTION

Super DRIVE® MV is formulated with the highest quality base oils and advanced additive technology to meet the demanding requirements of modern transmissions. **Super DRIVE® MV** is officially licensed and approved by Ford, and is designed to provide superior heat resistance, improved low-temperature fluidity, and enhanced vibration resistance compared to conventional automatic transmission fluids.

* BENEFITS / PROPERTIES

- Excellent protection and fluidity at low temperatures, enabling smooth gear shifts during cold starts.
- Contains additives that protect all components of automatic transmissions.
- Cleaner operation: Mercon V minimizes sludge and varnish deposits.
- Protects transmission seals and gaskets.
- Provides outstanding protection against transmission vibration.

* APPLICATIONS

Super DRIVE® MV lubricant is recommended for use in most automatic transmissions in Ford passenger vehicles and trucks (except those requiring MERCON SP, MERCON LV, or Type F fluid), including Lincoln and Mercury vehicles, as well as pre-2006 General Motors models and many imported vehicles.


TYPICAL CHARACTERISTICS

Super DRIVE® MV		
Color	VISUAL	Bright Red
Specific Gravity @ 20/4 °C	ATM D 1298	0.862
Flash Point, °C MIN.	ASTM D 92	185
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	37 7.3
Viscosity Index	ASTM D 2270	166

AVAILABLE IN:



**US Quart: 0.946 L*




**5 gal. Pail (19 L)*



**US Gal 3.785 L*



**55 gal. Drum (208 L)*



**5.0 Lt container*



**264 gal. IBC (1000 L)*

