

* DESCRIPTION

Super DRIVE® SAE 5W-40 API CK-4 is a high-performance lubricant for diesel engines or industrial applications that helps extend engine life under severe conditions, both on and off the road.

The advanced chemistry of this product delivers exceptional performance in engines requiring the API CK-4 service category, including those with exhaust gas recirculation (EGR), as well as certain marine applications.

* BENEFITS / PROPERTIES

- High-performance diesel applications, including turbocharged and low-emission engines designed before 2007, including those with EGR technology.
- On-highway operations under high-speed and high-load conditions, as well as short-haul pick-up and delivery cycles.
- Optimal performance in fleets using diesel engines from American and Japanese original equipment manufacturers (OEMs).
- Heavy-duty transport units, both on-road and off-road, including equipment for construction, mining, quarrying, and agriculture.

* APPLICATIONS

Super DRIVE® SAE 5W-40 oils are recommended for the lubrication of commercial vehicles and agricultural machinery, as well as for diesel engines in commercial vehicles and contractor equipment where a CK-4 or lower quality level is required.

Always consult the manufacturer's manual and follow its recommendations.

TYPICAL CHARACTERISTICS


Super DRIVE® 15W-40 API CK-4

SAE	-----	5W-40
Viscosity CCS, cP @ -20°C	ASTM D 5293	5900
Flash Point, °C	ASTM D 92	>220
Kinematic viscosity cSt @ 40 °C cSt @ 100 °C	ASTM D 445	95 - 100 14 - 15
Viscosity Index	ASTM D 2270	135-140
Pour Point, °C (°F)	ASTM D 97	- 33 (-27.4)
TBN, mg KOH/g	ASTM D 2896	11.2
Density @15.6°C, kg/l	ASTM D 4052	0.871
HTHS @150°C, cP	ASTM D 4683	3.9


* AVAILABLE IN:



****5.0 Lt container**



***5 gal. Pail (19 L)**



***Gal 3.785 L**



***55 gal drum (208 L)**



***264 gal. IBC (1,000 L)**

