

* DESCRIPTION

Super DRIVE® SAE 85W-140 are high-grade, multipurpose gear lubricants made from highviscosity index paraffinic base oils and blended with a unique extreme pressure (EP) additive that prevents wear. They contain oxidation, corrosion, and foam inhibitors.

These lubricants are excellent for all types of automotive and industrial bearings and gears, particularly those operating under severe temperature and load conditions. They are suitable for complete filling of limited slip differentials.

They provide excellent wear control even in the presence of small amounts of water and are recommended for use in truck transmissions and axles.

* BENEFITS / PROPERTIES

- Reduced wear.
- Low and high operating temperatures.
- Seal compatibility.
- One product for both axles and transmissions.


* APPLICATIONS

Super DRIVE® SAE 85W-140 meets the performance requirements of MIL-L-2105E, MACK GO-G and GO-H and the GL-5 service classification.

TYPICAL CHARACTERISTICS

Super DRIVE® 85W-140 API GL-5		
Specific Gravity @ 20/4 °C	ASTM D 1298	0.875
Kinematic Viscosity cSt @ 40 °C cSt @ 100 °C	ASTM D 445	341 25.0
Viscosity Index	ASTM D 2270	96
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	- 25

AVAILABLE IN:



****5 gal. Pail (19 L)***



****55 gal drum (208 L)***



****264 gal. IBC (1,000 L)***

