

* DESCRIPTION

These are multipurpose gear lubricants of optimal grade, manufactured from high-viscosity index paraffinic base oils. This oil is specifically designed for standard transmission gearboxes where extreme pressure performance is not required.

* BENEFITS / PROPERTIES

- Reduced wear.
- Lower operating temperatures.
- Compatibility with seals.
- Documented energy savings.
- Single product suitable for axles and transmissions.

* APPLICATIONS


These lubricants are intended for automotive and industrial bearings and gears, particularly those operating under high temperature and load conditions. They provide excellent wear control even in the presence of small amounts of water. Recommended for use in truck transmissions and axles.

TYPICAL CHARACTERISTICS

BELHERR® T-90 GL-1

Specific Gravity @ 25°C	ASTM D 1298	0.8960
Oil Viscosity @ 40°C, cSt	ASTM D 445	198
Oil Viscosity @ 100°C, cSt	ASTM D 445	17.5
ASTM Color, Max.	ATM D 1500	2.0
Viscosity Index	ASTM D 2270	95
Appearance	VISUAL	Bright
Color	VISUAL	Amber
Flash Point, °C	ASTM D 92	> 250
Pour Point, °C	ASTM D 97	- 13

AVAILABLE IN



Pail: 19 L



Drum: 208 L



Tote: 1,040 L